



### product description

Frame and blades are 6063 extruded aluminum alloy with 200-R1 satin anodized finish. The frame has a typical wall thickness of .050". The core is fully removable for easy installation.

This grille is available with blades set at 0°, 15° or 30°. Blades are 1/4" thick and spaced 1/2" on center. Mullion bars across the blades provide additional strength.

An optional opposed blade damper mounts through a series of spring clips and is screwdriver-operated through the face of the unit. The damper frame is separated from

See page LD-3 for core dimensions when used as a stand-alone product.

the blades with nylon bushings... this method of assembly eliminates corrosion and vibration.

To achieve a more equally balanced air flow across the face of the grille, an equalizing grid can be mounted on the damper and is available as an option.

Suitable for ceiling or sidewall application.

Core is fully removable. Installation is with screws that are installed through inner flange.

Available in clear anodized, white or a variety of custom colors.

### Listed Heights

(ins)	(mm)
1½	38
2	51
2½	64
3	76
3½	89
4	102
5	127
6	153
7	178
8	204
9	229
10	254
11	279
12	305

available options	depth of unit	test data
<b>LD-0°, 15°, 30°</b> Linear grille with blades fixed at 0°, 15° or 30° setting.		TD 6-7
<b>LD-OB-0°, 15°, 30°</b> Linear register with opposed blade damper. Damper requires 3" nominal minimum.		TD 6-7
<b>LD-OB-EG-0°, 15°, 30°</b> Linear register with opposed blade damper and equalizing grid.		TD 6-7

AIRGUIDE MANUFACTURING  
 795 WEST 20<sup>TH</sup> STREET  
 HIALEAH, FLORIDA 33010  
 PHONE: (305) 888-1631