



| HEIGHT (See Note) | | |
|----------------------|--------|-------|
| A | B | C |
| 6 3/4 | 4 3/16 | 4 7/8 |
| 7 3/4 | 5 3/16 | 5 7/8 |
| 8 3/4 | 6 3/16 | 6 7/8 |
| 9 3/4 | 7 3/16 | 7 7/8 |

- Diffusers are available as supply or return units for regressed or flush air handling Luminaires.
- Material: Galvannealed steel. Exposed slot area painted flat black.
- Diffuser (except 4 x 4 models) normally shipped fully assembled, ready for job site installation, specify for crossover and diffusers unassembled.
- Inlets: Standard 5" and 6" oval on side entry, round on top entry. Other sizes available on request.

| Luminaire Size | Air Diffuser Dim. | |
|----------------|-------------------|----|
| | W | L |
| 1 x 4 | 9 | 40 |
| 2 x 2 | 21 | 20 |
| 3 x 3 | 33 | 27 |
| 2 x 4 | 21 | 40 |
| 4 x 4 | 45 | 40 |

NOTE: Standard diffuser dimensions are stated. Dimensions A, B, C, W and L will vary with Luminaire manufacturer. To insure compatibility, list Luminaire manufacturer and model number. Ceiling clearance required is diffuser height plus 1/4" plus amount troffer slot is regressed above ceiling line. Top inlet units extend above this dimension.

options

- Steel un-insulated
- Steel with 1/2" internal insulation in diffuser
- Steel with 1/4" internal insulation
- Steel with 1/2" FSK external insulation

When ordering Air Guide Luminaire Diffusers, state product number (See above guide) and specify light fixture manufacturer and exact model number

*STANDARD SIZES (BASED ON FIXTURE MODEL)

| A | B |
|-------|-------|
| 6-3/4 | 4-5/8 |
| 7-3/4 | 5-5/8 |
| 8-3/4 | 6-1/8 |
| 9-3/4 | 7-1/2 |

*A and B Dimensions will vary according to light fixture Dimension

ordering instructions

