



product description

The PR series is an exceptional model in appearance and performance suited for cooling, heating and ventilating applications. The model PR-5 & 6 is a return air unit designed for concealed spline applications utilizing a fixed leg on two opposite sides with a locking tab on the remaining sides. All exposed surfaces are of aluminum

construction with the rear plenum being galvanized steel. The easily removable face allows access for duct connection. The model is available with a round, square or rectangular neck. Square opposed blade and round butterfly dampers are available for volume control where required. White finish is standard.

nomenclature for perforated products

- P = Perforated Diffuser
- R = Return
- S = Supply
- 1 = Round neck to fit 24" x 24" Grid – Standard T-Bar
- 2 = Square neck to fit 24" x 24" Grid – Standard T-Bar
- 10 = Round neck to fit 24" x 48" Grid – Standard T-Bar
- 20 = Square neck to fit 24" x 48" Grid – Standard T-Bar
- BFD = Butterfly damper used with round neck diffusers
- OB = Opposed blade damper used with square neck diffusers
- FGB = Fiberglass back diffusers
- NRF = Non-removable face
- PCRT = 22" x 22" and 46" x 22" sizes are suitable for 24" x 24" and 48" x 24" grid. Removable face with duct connection.
- P(S) or P(R)-3 = Round neck – surface mount for plaster or similar surface
- P(S) or P(R)-4 = Square neck – surface mount for plaster or similar surface
- P(S) or P(R)-5 = Round neck – spline mount (spline on two opposite sides)
- P(S) or P(R)-6 = Square neck – spline mount (spline on two opposite sides)
- P(S) or P(R)-7 = Round neck – spline mount with locking device
- P(S) or P(R)-8 = Square neck – spline mount with locking device
- P(S) or P(R)-11 = Round neck – tegular mount
- P(S) or P(R)-12 = Square neck – tegular mount

NOTE: All round neck prices are for diameters 4", 5", 6", 7", 8", 9", 10", 12", 14" and 16"

AIRGUIDE MANUFACTURING
795 WEST 20TH STREET
HIALEAH, FLORIDA 33010
PHONE: (305) 888-1631