




LINEAR BAR GRILLES

V-LINE LINEAR DIFFUSER

MODELS: VLD-S, VLD-S-OB, VLD-FM, VLD-FM-OB

SUSTAINABLE EXTRUDED ALUMINUM

Dimensions are in inches (mm)



MODEL:

VLD



- VLD-S**
V-line diffuser surface-mounted
- VLD-S-OB**
V-line diffuser surface-mounted with OB damper
- VLD-FM**
V-line diffuser flush-mounted
- VLD-FM-OB**
V-line diffuser flush-mounted with OB damper

DESCRIPTION:

1. Frame and blades are 6063 extruded aluminum alloy with 200-R1 satin anodized finish.
2. At the outer edge of the frame is a specially engineered channel which retains an extruded flexible vinyl bulb gasket that produces a positive air seal at the mounting surface, minimizing smudging. The mounting holes are dimpled, allowing for a counter-sunk fastener head appearance.
3. This diffuser is provided in a 1-way or 2-way air flow pattern and is available in 3, 6, 9 or 12" width with single sections up to 12' in length.
4. An optional OB damper mounts with a series of spring clips and is screwdriver-operated through the face of the unit. The damper frame is separated from the blades with injection-molded nylon bushings. This method of assembly eliminates corrosion and vibration.
5. Suitable for sidewall application.
6. Available in clear anodized, white or a variety of custom colors.

OPTIONS:

1. Finish
 - ANOD Clear Anodized
 - WHITE
 - MB Medium Bronze
 - B Black
 - Custom _____
2. Other
 - VLDT
 - VLDT-OB

PROJECT:

ENGINEER:

CONTRACTOR:

DATE

SERIES

DRAWING NO.