



OUTSIDE AIR LOUVERS

6" OUTSIDE AIR LOUVERS WITH DRAINABLE BLADE

MODELS: OL-6-DB-FL, OL-6-DB-CH

SUSTAINABLE EXTRUDED ALUMINUM

Dimensions are in inches

TOP & BOTTOM 2-5/8"
SIDES 3-1/4"

OL-6-DB-FL

Outside air louvers with drainable blades and flange frame.

TOP & BOTTOM 1-3/8"
SIDES 1-5/8"

OL-6-DB-CH

Outside air louvers with drainable blades and channel frame.

DESCRIPTION:

- High performance drainable blade 6" louver fabricated with mechanically joined 6063 extruded aluminum alloy.
- Frames are .125" with blades being .125".
- Blades are spaced 4" on centers at an angle of 38°.
- The blade design allows for excellent drainage of water through the horizontal gutter to the vertical drainage channel in the jambs and mullions.
- Standard finish is mill aluminum with a variety of anodized and high performance painted finishes available.
- Maximum one-piece construction is 12' wide x 8' high. Joining mullions are furnished for larger sizes.

OPTIONS:

1. Finish

- White
- ANOD Clear Anodized
- Medium Bronze
- Black
- Custom _____

2. Options

- OBFL (Fire link)
- Expanded Aluminum Bird Screen
- Woven Fiberglass Insect Screen
- Filter Frame
- Opposed Blade Damper

PROJECT:			
ENGINEER:	DATE	SERIES	DRAWING NO.
CONTRACTOR:			